

Hot water high-pressure cleaner

Performance Pro




- 4 poles electrical motor (1450 RPM) and thermal protection
- Three ceramic pistons, brass linear pump head with built-in (Interchangeable seat) by-pass valve
- Suction and delivery S/S valves
- Max water inlet temperature 40°C
- Safety valve
- Auxiliary motor for burner, air-cooling and two way fuel pump
- Stainless steel vertical burner with high thermal efficiency
- Refilling tank
- Delayed and 24V low voltage Automatic Stop System
- Adjustable detergent delivery with built-in tank for direct suction (high pressure delivery)
- Glycerine pressure gauge
- Power cable (7 m)
- High precision digital temperature setting for burner
- Gun with swivel hose fitting and water flow regulation for steam function
- Low tension control switches
- Digital control panel with operating hours counter; display to monitor motor, burner and low fuel cut-out; fault indicator; anti-leakage device with power cut-off
- Tough steel main frame

Optional:

- Hose-reel with brake for 40m hose

	Performance Pro 1515	Performance Pro 2015
Product No.	8.621.0902	8.621.0903
Voltage	400V	400V
Wattage	5500W	7300W
Operat. Pressure / Max	30-150 Bar	30-200 Bar
Flow Rate	660 Ltrs/h	660 Ltrs/h
Max. Temp.	140°C	140°C
Motor Speed	1450 rpm	1450 rpm
Machine dimensions / Weight	94x65x90cm / 114Kg	94x65x90cm / 116Kg



Morclean Ltd, Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield S43 3JN, UK.
 Tel: +44 (0)1246 471147 Fax: +44 (0)1246 471277 sales@morclean.co.uk www.morclean.co.uk
 Registered in England No.465133

Morclean reserve the rights to update and amend the specification of any of our equipment & accessories in the interest of the customer. All prices subject to VAT @ SR. (E & O.E)