

Hot water high-pressure cleaner

Performance Pro/HT



Optional
Hose-reel with brake

- 4 poles electrical motor (1450 RPM) with thermal protection
- Three ceramic pistons, brass linear pump head with built-in by-pass valve
- Suction and delivery S/S valves
- Safety valve
- Auxiliary motor for burner air-cooling and two ways fuel pump
- Vertical burner with high thermal efficiency (>90%) designed for high flow rates
- Max thermal power 88 kW
- Anti-scale device with refilling tank
- Delayed and 24V low voltage
- Automatic Stop System
- Adjustable detergent delivery with built-in tank for direct suction (high pressure delivery)
- Glycerine pressure gauge
- Power cable (5m)
- Temperature regulation gauge
- Gun with swivel hose fitting
- Low tension control switches
- Tough steel main frame

Optional:

- Hose-reel with brake
- Antiscale LC-PRECAL (pcs. 4 x 5 Lt.) code 3.697.0044



Tilting cover



Vertical burner



Header tank & antiscale devise

	Performance Pro HT 1521	Performance Pro HT 2021
Product No.	8.623.0903	8.623.0901
Voltage	400V	400V
Wattage	7300W	9700W
Pressure	150 bar	200 bar
Delivery Rate	630-1260 Ltrs/h	630-1260 Ltrs/h
Max. Temp.	140°C	140°C
Motor Speed	1450 rpm	1450 rpm
Machine dimensions / Weight	125x69x89cm / 153Kg	125x69x89cm / 158Kg



ask about
our full range
of chemicals
& detergents

CALL FREE ON
0800 1300 402
to arrange a visit to our
working showroom
and demo area

Morclean Ltd, Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield S43 3JN, UK.
Tel: +44 (0)1246 471147 Fax: +44 (0)1246 471277 sales@morclean.co.uk www.morclean.co.uk
Registered in England No.465133

Morclean reserve the rights to update and amend the specification of any of our equipment & accessories in the interest of the customer. All prices subject to VAT @ SR. (E & O.E)