

Fixed Cold Water High Pressure Washing Unit

Powerfix



- 4 poles electric motor (1450 RPM) and thermal protection
- Three ceramic coated pistons, brass axial pump head with built-in interchangeable seat) by-pass valve
- Stainless steel suction and delivery valves
- Delayed Automatic Stop System, 24 V low voltage (1613.2015 version only)
- Pressure accumulator
- Adjustable double detergent/wax selector
- Max. water inlet temperature 40°C

Optional:

- Hose reel
- Version with high pressure detergent supply tank
- Stainless steel version



	Powerfix 125/11	Powerfix 160/13	Powerfix 200/15
Code	8.653.0001	8.653.0002	8.653.0003
Operator pressure	30/125 bar	30/160 bar	30/200 bar
Operator pressure	435/1813	435/2320	435/2900
Delivery rate	660 l/h or 11 l/m	780 l/h or 13 l/m	900 l/h or 15 l/m
abs. power	3000W	4500W	7000W
RPM	1450	1450	1450
Voltage	230V-50Hz	400V-50Hz	400V-50Hz

	Stainless Steel Version
S-Line 125/11S	code 8.653.0004
S-Line 160/13S	code 8.653.0005
S-Line 200/15S	code 8.653.0006



**CALL FREE ON
0800 1300 402**
to arrange a visit to our
working showroom
and demo area

Morclean Ltd, Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield S43 3JN, UK.
Tel: +44 (0)1246 471147 Fax: +44 (0)1246 471277 sales@morclean.co.uk www.morclean.co.uk
Registered in England No.465133

Morclean reserve the rights to update and amend the specification of any of our equipment & accessories in the interest of the customer. All prices subject to VAT @ SR. (E & O.E)