

Cold water high-pressure cleaners

GNX 22



GNX 22

- Two stage motor • Suction system with by-pass cooling
- Stainless steel tank
- Comes complete with standard set of accessories • Quiet operation • Handy accessory holder • Blower available

Standard Accessories:

- 2 m 35 mm dia. flexible hose • 2 x 0.5 m chromium plated steel extension pipe • Curve with unload valve • Holder for floor accessories • Water brush • D.35 nozzle • D.35 lance • Cloth filter • Foam filter • Stainless steel combined brush • D.35 mm round brush



	GNX 22	GB 32
Product No.	8.202.0001	8.204.0006
Motor W	1200 (max 1400)	1200 (max 1400)
Column depression	2150 mm H ₂ O (21.09 kPa)	1650 mm H ₂ O (16.19 kPa)
Suction	50 l/s	61 l/s
Tank capacity l/gal.	20/5.29	30/8.46
Voltage	230 V-50 Hz	230 V-50 Hz

GB 32

- Silenced motor
- Suction system with by-pass cooling
- Power tool socket (max. 1800 W) with board for vacuum unit shut down • Handy 4 m flexible hose

Standard Accessories:

- 4 m 35 mm dia. flexible hose • 2 x 0.45 m chromium plated steel extension pipes • Holder for floor accessories • Bristle brush • D.35 nozzle • D.35 lance • Cloth filter • Foam filter • Water brush • Cartridge filter



Power tool socket

Impact-resistant tank

