

TANKS & INTERCEPTORS

Vehicle Wash Interceptor with Partial Treatment for Oils

Used for partial treatment where wash water contains higher levels of oils or grease.

Features

Water conditioning aluminium sulphate dosing to neutralise detergents and split emulsions. Fitted with coalescent filter.



The system can be installed in conjunction with the wash system to provide accurate dosing.



This product requires frame(s) and cover(s)					
Model/type	Size mm	Duty	European Standard	Loading	Typical Overground
A15	600 x 450	light duty	BSEN 124	3 tonne approx.	cars & small vans
B125	600 x 450	medium duty	BSEN 124	17 tonne approx.	vans & small commercial
D400	600 x 450	heavy duty	BSEN 124	38 tonne approx.	large commercial/HGV

Getting it there...

Specialised equipment, often an awkward shape or size, needs specialist delivery. In order to ensure that critical equipment arrives intact, on time, and unloaded carefully at the right location, we transport equipment to be installed ourselves using our own vehicles.



**CALL FREE ON
0800 4584091
to arrange a visit to our
working showroom
& demo area**

Morclean Ltd, Stephenson Road, Speedwell Industrial Estate, Staveley, Chesterfield S43 3JN, UK.
Tel: +44 (0)1246 471147 Fax: +44 (0)1246 471277 sales@morclean.co.uk www.morclean.co.uk
Registered in England No.465133

Morclean reserve the rights to update and amend the specification of any of our equipment & accessories in the interest of the customer. All prices subject to VAT @ SR. (E & O.E)